

Certificate of constancy of performance

0036-CPR-RG05-13**Revision 01**

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Powered smoke and heat exhaust ventilator model range: RDM 57 ... D temperature time class: F600 models

RDM 57-2528 ... D	RDM 57-2531 ... D	RDM 57-3535 ... D
RDM 57-3540 ... D	RDM 57-3545 ... D	RDM 57-4550 ... D
RDM 57-4556 ... D	RDM 57-5663 ... D	RDM 57-5671 ... D
RDM 57-7180 ... D	RDM 57-7190 ... D	RDM 57-9090 ... D

(Application classes see annex 1 for this certificate)

produced by or for

**Nicotra Gebhardt GmbH
Gebhardtstraße 19 - 25
D-74638 Waldenburg**

in the manufacturing plant

**Nicotra Gebhardt GmbH
Gebhardtstraße 19 - 25
D-74638 Waldenburg**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performance described in Annex ZA of the standard

EN 12101-3:2015

under system 1 are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on 2016-12-29 and will remain valid till 2026-12-31, as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Munich / 2021-12-01



Andreas Klotz
Deputy Head of Certification Body for
Construction Products



Industrie Service

Model	Temperature/time classification according to EN 12101-3	Snow load class	Wind load	Application classes ^{*1}
RDM 57-2528 ... D	F600	SL 1000	-	ND, LB
RDM 57-2531 ... D	F600	SL 1000	-	ND, LB
RDM 57-3535 ... D	F600	SL 1000	-	ND, LB
RDM 57-3540 ... D	F600	SL 1000	-	ND, LB
RDM 57-3545 ... D	F600	SL 1000	-	ND, LB
RDM 57-4550 ... D	F600	SL 1000	-	ND, LB
RDM 57-4556 ... D	F600	SL 1000	-	ND, LB
RDM 57-5663 ... D	F600	SL 1000	-	ND, LB
RDM 57-5671 ... D	F600	SL 1000	-	ND, LB
RDM 57-7180 ... D	F600	SL 1000	-	ND, LB
RDM 57-7190 ... D	F600	SL 1000	-	ND, LB
RDM 57-9090 ... D	F600	SL 1000	-	ND, LB

^{*1}: caption to application classes:

LB: dual purpose ventilator

AB: for use outside smoke reservoir

ND: only for use on a rooftop

NA: only for use in an outer wall

VA: applicable for vertical drive shaft position

HA: applicable for horizontal drive shaft position

ZB: Forced ventilation for motor over cooling duct necessary

IF: for use outside a building

WG: insulated ventilator

BG: only on top of heated buildings

IB: for use inside smoke reservoir

